



## EU - Type Examination Certificate

(1)

(2)

Equipment or Protective Systems Intended for Use  
in Potentially Explosive Atmospheres  
(Directive 2014/34/EU)

(3) EU - Type Examination Certificate number:

**FTZÚ 16 ATEX 0089X**

(4) Product: **Flameproof luminaire type PITBUL-Ex-LED; PITBUL-Ex-Em-LED  
and MULTIPITBUL-Ex-LED**

(5) Manufacturer: **VYRTYCH a.s.**

(6) Address: **Bělehradská 314/18, 140 00 Praha 4 - Nusle, Czech Republic**

(7) This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

(8) The Physical-Technical Testing Institute, Notified Body number 1026, in accordance with Articles 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26.02.2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Report number:

**16/0089 dated 15.08.2016**

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

**EN 60079-0:2012, EN 60079-1:2014, EN 60079-7:2015, EN 60079-11:2012, EN 60079-18:2015,  
EN 60079-31:2014, EN 60079-28:2015**

(10) If the sign "X" is placed after the certificate number, it indicates that the product is subject to Specific Conditions of Use specified in the schedule to this certificate.

(11) This certificate relates only to the design and construction of the specified product. Further requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by this certificate.

(12) The marking of the product shall include the following:

 **II 2G Ex db eb ib mb op is IIC T4 Gb** – see clause 15

 **II 2D Ex tb IIIC T67°C Db**

This certificate is valid till: **31.08.2021**

Responsible person:

  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 16.08.2016

Page: 1/3

Annex: No. 1 (2 sheets)

This certificate is granted subject to the general conditions of the FTZÚ, s.p.  
This certificate may only be reproduced in its entirety and without any change, schedule included.



**Physical-Technical Testing Institute  
Ostrava - Radvanice**

(13) **Schedule**

(14) **EU - Type Examination Certificate No. FTZÚ 16 ATEX 0089X**

(15) Description of Product:

The flameproof luminaire type Pitbul-Ex-LED, Pitbul-Ex-Em-LED (non-maintained emergency lighting) and MultiPitbul-Ex-LED (maintained emergency lighting) with degree of protection IP 65 is composed of three parts which comprises a body (varnished steel plate or stainless steel plate of thickness 1mm) equipped by countersink-head rivets with internal screws and with gasket, glass light transmitting cover which is fixed to the body by screws and varnished steel plate (reflector). On body ends are inserted plastic or stainless steel Ex-cable glands or plugs – see Annex No.1.

Inside of body are installed one or two 2x multi-pole terminal block WAGO type 262-283 or 262-233 (PTB 98 ATEX 3125U) in type of Ex-protection Ex e II, for connection of cable conductors to 4 mm<sup>2</sup>, electronic ballast BAREL type HFX LED (HFxE LED for emergency lighting) (Presafe 14 ATEX 5355U) in type of Ex-protection Ex eb mb II and the flameproof battery set type VBA-Ex-NiCd 4,8V /4Ah in type of Ex-protection Ex mb II T5 Gb (FTZÚ 10 ATEX 0145X/2). The luminaire can be alternative equipped by Watchdog unit CG-S module in Ex-protection II 2G Ex e ib mb IIC (PTB 04 ATEX 2110U).

The reflector, according to type variant of luminaire, can be quipped by one or two off-load switch type VOD-Ex (FTZÚ 10 ATEX 0297U) alternatively type 07-1544 (PTB 99 ATEX 1011U) in type of Ex-protection Ex db IIC. As the light sources are used LED modules type ARC 600 (25W) or ARC 1200 (50W) (Presafe 15 ATEX 6296U) in type of Ex-protection Ex mb op is IIC T4 Gb.

Electrical parameters:

Nominal Voltage: 110-254V AC; 50/60Hz; or 220-250V DC; 0,11-0,55A

Ex marking of product:

- II 2G Ex db eb mb op is IIC T4 Gb – luminaire with off-load switch;
- II 2G Ex db eb ib mb op is IIC T4 Gb – luminaire with off-load switch and Watchdog unit CG-S module;
- II 2G Ex eb mb op is IIC T4 Gb – luminaire without off-load switch and Watchdog unit CG-S module.

**CODING OF TYPE PITBUL-EX- LED LUMINAIRE**

Type coding	Type
PITBUL-Ex-LED-XXXX-YYY*-D	A type luminaire with off-load switch
PITBUL-Ex-LED-XXXX-YYY - WOD	A type luminaire without off-load switch
MULTIPITBUL-Ex-LED-XXXX-YYY - D	A type luminaire (maintained emergency lighting) with off-load switch
MULTIPITBUL-Ex-LED-XXXX-YYY- WOD	A type luminaire (maintained emergency lighting) without off-load switch
PITBUL- Ex- Em - LED - XXXX-YYY	A type luminaire (non-maintained emergency lighting)

\*XXXX - marking of luminous flux (lm)

YYY - marking of type body of luminaire

Responsible person:

Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 16.08.2016

Page: 2/3

Annex: No. 1 (2 sheets)

This certificate is granted subject to the general conditions of the FTZÚ, s.p.  
This certificate may only be reproduced in its entirety and without any change, schedule included.



Physical-Technical Testing Institute  
Ostrava - Radvanice

(13)

Schedule

(14) **EU - Type Examination Certificate No. FTZÚ 16 ATEX 0089X**

(16) Report Number.: 16/0089

(17) Specific Conditions of Use:

1. The type luminaire without installed off-load switch must be labelled "Do not open when energized".
2. Ambient temperature  $T_{amb}$ :
  - 20°C to +60°C for type PITBUL-Ex-LED; 1x 25W/50W,
  - 20°C to +55°C for type PITBUL-Ex-LED; 2x 25W/50W,
  - 0°C to +40°C for type PITBUL-Ex-Em-LED; 1x 25W/50W,
  - 0°C to +40°C for type MULTIPITBUL-Ex-LED; 1x 25W/50W,
  - 0°C to +35°C for type MULTIPITBUL-Ex-LED; 2x 25W/50W.
3. The luminaire is intended for fixed installation and must be labelled "Warning - potential danger of electrostatic charging" - see Technical conditions.
4. The Technical conditions of maintenance must be complied.

(18) Essential Health and Safety Requirements:

Compliance with the Essential Health and Safety Requirements is covered by standards mentioned in clause (9) of this certificate.

(19) Drawings and Documents:

Number	Issue	Sheets	Date	Description
	00	8	08.08.2016	Technical description
	01	1	05.08.2016	Technical conditions
Assembly PITBUL-Ex-LED	01		09.08.2016	Drawing
Labels		2	05.08.2016	Drawing

Responsible person:

  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 16.08.2016

Page: 3/3

Annex: No. 1 (2 sheets)

This certificate is granted subject to the general conditions of the FTZÚ, s.p.  
This certificate may only be reproduced in its entirety and without any change, schedule included.



Physical-Technical Testing Institute  
Ostrava - Radvanice

**ANNEX No. 1**

**to EU - Type Examination Certificate No. FTZÚ 16 ATEX 0089X**

**List of used components (Cable gland and blanking element)**

Manufacturer	Component	Type (series)	Certificate ATEX
OBO	cable glands	V-TEC EX	PTB 99 ATEX 3112X
OBO	cable glands	V-TEC EX-; M16x1,5	PTB 99 ATEX 3113X
Hummel AG	cable glands	HSK-K-MZ-Ex, HSK-M-Ex, HSK-M-PVDF-Ex, HSK-M-EMV-Ex, HSK-M-EMV-PVDF-Ex, HSK-M-EMV-D-Ex, HSK-MZ-Ex, HSK-MZ-PVDF-Ex, HSK-MZ-EMV-Ex, HSK-MZ-EMV-PVDF-Ex, HSK-INOX-Ex, HSK-INOX-PVDF-Ex, HSK-INOX-EMV-Ex and HSK-INOX-EMV-PVDF-Ex	KEMA 99 ATEX 6971X
Hummel AG	cable glands	EXIOS;EXIOS MZ	BVS 10 ATEX E 062X
Hummel AG	blanking elements	V-...-Ex-d, RSD	KEMA 06 ATEX 0024
EATON	cable glands	GHG 960..R.... ; M12-M16	PTB 99 ATEX 3101X
EATON	cable glands	GHG 960..R.... ; M20-M63	PTB 99 ATEX 3128X
EATON	cable glands	ADE-.....	INERIS 12 ATEX 0032X
EATON	blanking elements	CK; CQ	SIRA 10 ATEX 1225X
EATON	blanking elements	GHG 960 1927 R....	PTB 01 ATEX 1128X
EATON	blanking elements	DP-E	SIRA 99ATEX3050X
WISKA	cable glands	*SKE/1(S)(-L)*(-RDE) ** (LT) (**-***)	PTB 13 ATEX 1015 X
WISKA	cable glands	*SSKE(S)(-L)(-4)(-RDE) **(-**) (LT) (****)	PTB 05 ATEX 1098 X
WISKA	cable glands	EMSKEZ	PTB 09 ATEX 1049
WISKA	cable glands	WEID.E1XF	NEMKO 02 ATEX 501 X
WISKA	cable glands	WEID.E1WF	NEMKO 02 ATEX 500 X
WISKA	blanking elements	OSSP	NEMKO 02 ATEX 502
WISKA	blanking elements	OSRA	NEMKO 03 ATEX 1458
WISKA	blanking elements	OSAJ	NEMKO 03 ATEX 1459X
WISKA	blanking elements	EX-VSM	PTB 03 ATEX 1158
WISKA	blanking elements	EX-EMVS	PTB 05 ATEX 1106
WISKA	blanking elements	EX-EVSG	PTB 06 ATEX 1032 X
WISKA	blanking elements	EX-KEM	PTB 04 ATEX 1040 X
WISKA	cable glands	OSNJ	NEMKO 03 ATEX 1460 X
WISKA	cable glands	*MSKE(S)(-L)(-**-RDE) **(-**) (LT) (****)	PTB 04 ATEX 1112 X
Pflitsch	cable glands + blanking elements	Ex e	PTB 06 ATEX 1036X

Responsible person:

  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 16.08.2016

Page: 1/2

This certificate is granted subject to the general conditions of the FTZÚ, s.p.  
This certificate may only be reproduced in its entirety and without any change, schedule included.



Physical-Technical Testing Institute  
Ostrava - Radvanice

**ANNEX No. 1**

**to EU - Type Examination Certificate No. FTZÚ 16 ATEX 0089X**

Manufacturer	Component	Type (series)	Certificate ATEX
BIMED	cable glands	DORADO	IMQ 11 ATEX 036
BIMED	cable glands	ORION	IMQ 11 ATEX 037
BIMED	cable glands	OCTANS	IMQ 11 ATEX 038X
BIMED	cable glands	ORION UNIVERSAL; CRATER	CESI 13 ATEX 033X
BIMED	cable glands	E-OCTANS; E-VELA; NORMA; E-CARINA; E-CYGNUS	IMQ 13 ATEX 018X
BIMED	cable glands	PHOENIX	IMQ 13 ATEX 029X
BIMED	cable glands	LYRA	IMQ 13 ATEX 010X
BIMED	cable glands	GEMINI; DRACO; CETUS	MQ 13 ATEX 011X
BIMED	blanking elements	APUS; GRUS; ARIES; PAVO; AQUILA	CESI 13 ATEX 066
BIMED	cable glands	HYDRA	IBExU 10 ATEX 1169U
ELFIT	cable glands	UNI; UNP; UNN; XP; XPA	CESI 03 ATEX 305X
ELFIT	cable glands	F.....	CESI 00 ATEX 075X
ELFIT	cable glands	REV; REVD	CESI 13 ATEX 019X
ELFIT	cable glands	UN...	IMQ 16 ATEX 005 X
Peppers	cable glands	A8*F, A8C**F, D8X*F, E8X*F	SIRA 01 ATEX 1270X
Peppers	cable glands	E****F*, D****F, C****E*	SIRA 01 ATEX 1271X
Peppers	cable glands	A****, A*L**, A*LC***, A*RC***	SIRA 01 ATEX 1272X
Peppers	cable glands	UL-C; UL-X; UL-U	SIRA 09 ATEX 1066X
Peppers	cable glands	CR-***, CR-D**, CR-O***	SIRA 03 ATEX 1479X
Peppers	blanking elements	SPA, SPB, SPHH, SPMH	SIRA 09 ATEX 1320X
Peppers	blanking elements	ACDP	SIRA 09 ATEX 3321U
HAWKE	cable glands	501/421; 501/423; 501/453	BASEEFA 06 ATEX 0056X
HAWKE	cable glands	501/453/UNIVERSAL	BASEEFA 06 ATEX 0057X
HAWKE	cable glands	ICG 6xx	BASEEFA 06 ATEX 0058X
HAWKE	blanking elements	375	BASEEFA 12 ATEX 0095X
HAWKE	blanking elements	390	BASEEFA 11 ATEX 0157X
HAWKE	blanking elements	487	BASEEFA 11 ATEX 0149X
HAWKE	blanking elements	475; 477	BASEEFA 10 ATEX 0262X
HAWKE	blanking elements	387	BASEEFA 06 ATEX 0118U

Responsible person:

*Lukáš Martinák*  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 16.08.2016

Page: 2/2



(1) **Supplementary EU - Type Examination Certificate No.1**

(2) **Equipment or Protective Systems Intended for Use  
in Potentially Explosive Atmospheres  
(Directive 2014/34/EU)**

(3) EU - Type Examination Certificate number:

**FTZÚ 16 ATEX 0089X**

(4) Product: **Flameproof luminaire type PITBUL-Ex-LED; PITBUL-Ex-Em-LED  
MULTIPITBUL-Ex-LED and PITBUL-Ex-LED-FROST**

(5) Manufacturer: **VYRTYCH a.s.**

(6) Address: **Židněves 116, 294 06 Březno, Czech Republic**

(7) This supplementary certificate extends EU - Type Examination Certificate No. FTZÚ 16 ATEX 0089X to apply to products designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.

(8) The Physical-Technical Testing Institute, Notified Body number 1026, in accordance with Articles 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26.02.2014, certifies that this product, as modified by this supplementary certificate, has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

**EN 60079-0:2012+A11:2013, EN 60079-1:2014, EN 60079-7:2015, EN 60079-11:2012,  
EN 60079-18:2015, EN 60079-31:2014, EN 60079-28:2015**

(10) If the sign "X" is placed after the certificate number, it indicates that the product is subject to Specific Conditions of Use specified in the schedule to this certificate.

(11) The marking of the product shall include the following:

 **II 2G Ex db eb ib mb op is IIC T4 Gb** – see the main certificate

 **II 2D Ex tb op is IIC T67°C Db**

(12) This certificate is valid till: **28.02.2024**

Responsible person:

  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 22.02.2019

Page: 1/3



Physical-Technical Testing Institute  
Ostrava - Radvanice

(13)

Schedule

(14) **Supplementary EU - Type Examination Certificate No. 1  
to FTZÚ 16 ATEX 0089X**

(15) Description of the variation to the Product:

The subject of this supplementary certificate is:

- Modification of certified apparatus;
- Change of manufacturer's address;
- Prolongation of certificate validity.

Added variant of luminaire PITBUL-Ex-LED-FROST-xxxx 218/236/418/436 for ambient temperature from -40°C. The electrical equipment does not contain off-load switch and emergency module with battery pack.

Ex marking for this variant:  $\text{Ex}$  II 2G Ex eb ib mb op is IIC T4 Gb.

Electrical parameters are unchanged.

**CODING OF TYPE LUMINAIRE PITBUL-EX- LED FROST**

PITBUL – Ex – LED – FROST-XXXX-YYY	A type luminaire without off-load switch
------------------------------------	--

\*XXXX - marking of luminous flux (lm)

YYY - marking of type body of luminaire

The manufacturer's address was changed from: Bělehradská 314/18, 140 00 Praha 4 – Nusle to new address: Židněves 116, 294 06 Březno.

(16) Report Number.: 16/0089/1

(17) Specific Conditions of Use:

None additional to those listed previously.

1. Added Ambient temperature range: -40°C ≤ Tamb ≤ +60°C for variant PITBUL-Ex-LED-FROST-xxxx-218/236 and -40°C ≤ Tamb ≤ +55°C for variant PITBUL-Ex-LED-FROST-xxxx-418/436.

(18) Essential Health and Safety Requirements:

Compliance with the Essential Health and Safety Requirements is covered by standards mentioned in clause (9) of this supplementary certificate.

Responsible person:

  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 22.02.2019

Page: 2/3



Physical-Technical Testing Institute  
Ostrava - Radvanice

(13)

Schedule

(14) **Supplementary EU - Type Examination Certificate No. 1  
to FTZÚ 16 ATEX 0089X**

(19) Drawings and Documents:

Number	Sheets	Issue	Date	Description
--	9	00	12.02.2019	Technical description
--	2	03	04.02.2019	Technical conditions for mounting
PITBUL-Ex-LED-FROST	1	--	18.12.2018	Drawing
Labels	3	c)	18.12.2018	Drawing

Responsible person:

  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 22.02.2019

Page: 3/3





(1) **Supplementary EU - Type Examination Certificate No.2**

(2) **Equipment or Protective Systems Intended for Use  
in Potentially Explosive Atmospheres  
(Directive 2014/34/EU)**

(3) EU - Type Examination Certificate number:

**FTZÚ 16 ATEX 0089X**

(4) Product: **Flameproof luminaire type PITBUL-Ex-LED; PITBUL-Ex-LED-Em,  
MULTIPITBUL-Ex-LED and PITBUL-Ex-LED-FROST**

(5) Manufacturer: **VYRTYCH a.s.**

(6) Address: **Židněves 116, 294 06 Březno, Czech Republic**

(7) This supplementary certificate extends EC - Type Examination Certificate No. FTZÚ 16 ATEX 0089X to apply to products designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.

(8) The Physical-Technical Testing Institute, Notified Body number 1026, in accordance with Articles 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26.02.2014, certifies that this product, as modified by this supplementary certificate, has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

(9) In accordance with Article 41 of Directive 2014/34/EU, EC-Type Examination Certificates referring to 94/9/EC that were in existence prior to the date of application of 2014/34/EU (20.04.2016) may be referenced as if they were issued in accordance with Directive 2014/34/EU. Supplementary Certificates to such EC-Type Examination Certificates, and new issues of such certificates, may continue to bear the original certificate number issued prior to 20.04.2016.

(10) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:  
**EN IEC 60079-0:2018, EN 60079-1:2014, EN 60079-7:2015, EN 60079-11:2012, EN 60079-18:2015,  
EN 60079-31:2014, EN 60079-28:2015**


If the sign "X" is placed after the certificate number, it indicates that the product is subject to Specific Conditions of Use specified in the schedule to this certificate.

(11) The marking of the product shall include the following:

 **II 2G Ex db eb ib mb op is IIC T4 Gb - see (15)**  
**II 2D Ex tb op is IIC T67°C Db**

(12) This certificate is valid till: **31.01.2026**

Responsible person:

  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 26.01.2021

Page: 1/3



**Physical-Technical Testing Institute  
Ostrava - Radvanice**

(13)

**Schedule**

(14) **Supplementary EU - Type Examination Certificate No. 2  
to FTZÚ 16 ATEX 0089X**

(15) Description of the variation to the Product:

The subject of this supplementary certificate is:

- Modification of certified apparatus;
- Evaluation according to the newest standards;
- Prolongation of certificate validity.

This supplementary certificate describes of using new version of LED module with marking BG4 as a basic used component, existing LED module with marking BG3 shall be used as alternative component.

Ambient temperature range was increased to +50°C for variant PITBUL-Ex-LED-Em.

Design, type marking and electrical parameters of luminaire mentioned in the basic and Supplement No.1 of the certificate are unchanged.

The luminaire is verified according to new standard EN IEC 60079-0:2018.

Ex marking of product:

- II 2G Ex db eb mb op is IIC T4 Gb – luminaire with off-load switch;
- II 2G Ex db eb ib mb op is IIC T4 Gb – luminaire with off-load switch and Watchdog unit CG-S module;
- II 2G Ex eb mb op is IIC T4 Gb – luminaire without off-load switch and Watchdog unit CG-S module.

**CODING OF TYPE PITBUL-EX- LED LUMINAIRE**

Type coding	Type
PITBUL-Ex-LED-XXXX*-YYY*-D	A type luminaire with off-load switch
PITBUL-Ex-LED-XXXX-YYY-WOD	A type luminaire without off-load switch
MULTIPITBUL-Ex-LED-XXXX-YYY-D	A type luminaire (maintained emergency lighting) with off-load switch
MULTIPITBUL-Ex-LED-XXXX-YYY-OD	A type luminaire (maintained emergency lighting) without off-load switch
PITBUL-Ex-LED-Em-XXXX-YYY	A type luminaire (non-maintained emergency lighting)
PITBUL-Ex-LED-FROST-XXXX-YYY	A type luminaire without off-load switch

\*XXXX - marking of luminous flux (lm)

\*YYY - body type marking of luminaire

Responsible person:

Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 26.01.2021

Page: 2/3

This certificate is granted subject to the general conditions of the FTZÚ, s.p.  
This certificate may only be reproduced in its entirety and without any change, schedule included.



Physical-Technical Testing Institute  
Ostrava - Radvanice

(13)

Schedule

(14) **Supplementary EU - Type Examination Certificate No. 2  
to FTZÚ 16 ATEX 0089X**

(16) Report Number: 16/0089/2

(17) Specific Conditions of Use:

1. Ambient temperature range:

-20°C ≤ Tamb ≤ +60°C	PITBUL-Ex-LED-XXXX-218/236
-20°C ≤ Tamb ≤ +55°C	PITBUL-Ex-LED-XXXX-418/436
0°C ≤ Tamb ≤ +50°C	PITBUL-Ex-LED-Em-XXXX-218/236
0°C ≤ Tamb ≤ +40°C	MULTIPITBUL-Ex-LED-XXXX-218/236
0°C ≤ Tamb ≤ +35°C	MULTIPITBUL-Ex-LED-XXXX-418/436
-40°C ≤ Tamb ≤ +60°C	PITBUL-Ex-LED-FROST-XXXX-218/236
-40°C ≤ Tamb ≤ +55°C	PITBUL-Ex-LED-FROST-XXXX-418/436

- The luminaire is intended for fixed installation and must be labelled "Warning - potential danger of electrostatic charging" - see Technical conditions for mounting.
- The type luminaire without installed off-load switch must be labelled "Do not open when energized".
- The Technical conditions for mounting must be complied.


(18) Essential Health and Safety Requirements:

Compliance with the Essential Health and Safety Requirements is covered by standards mentioned in clause (10) of this supplementary certificate.

(19) Drawings and Documents:

Number	Revision	Sheets	Date	Description
--	02	9	23.11.2020	Technical description
--	05	2	01.12.2020	Technical conditions for mounting
Labels	e	3	02.12.2020	Drawing

Responsible person:

  
Dipl. Ing. Lukáš Martinák  
Head of Certification Body



Date of issue: 26.01.2021

Page: 3/3